



Thermal Printers

Perfect Image®

*...the fastest throughput, lowest print cost
and finest thermal technology available
today for CD-R and DVD-R printing.*

Perfect Image® AutoPrinter™

Automated for lights-out
production. (120 disc capacity).



Perfect Image® Prism™ Printer

The world's only full-color thermal printer.

- ✓ **Full Color, Indelible** instant-dry process delivers unequaled silk-screen like quality and professional finish.
- ✓ **Twice as Fast** as any other thermal printer for true production throughput.
- ✓ **Unequaled Durability** provides reliable 24-hour, 7-day high-volume production.
- ✓ **Low, Low Print Costs** of 1.1 cents per disc and over 6000 discs per ribbon with ribbon-saver feature.
- ✓ **Complete Custom Design Flexibility** with full color, 2-color, one color, spot color, customized text and graphics, merge fields, and optional aligned printing on pre-screened discs.

CONVERG

Rimage's leadership in software,
hardware, applications and service
converge to continually make the
best better.



R I M A G E™

*"It's cleaner, neater, sharper and quicker than ink jet.
Rimage thermal print wins hands down."*

— Royal Scanlon, RSRT, Inc.

*"The Rimage thermal transfer printer has emerged as the
product of choice for high-volume production applications."*

— Steve Nathans, eMedia Professional, June 2000

We have the look!

Whether it's one line of customized text or full color graphics, Rimage delivers excellent results on all standard CD-R and DVD-R media.




Ribbon-Saver Feature 1-2 lines of text

Prints over 6000 discs/ribbon
Print cost: 1¢ each




Spot Color 2-color

Prints 750 discs/ribbon
Print cost: 12½¢ each



Mono Ribbon Single color

Prints 1500 discs/ribbon
Print cost: 4½¢ each



Full Color

Prints 500 discs/ribbon
Print cost: 25¢ each



Producer Prostar

Rimage Prism printers are standard on all Rimage automated CD-R/DVD-R publishing systems. Offering full color data-to-print accuracy in true "lights-out" production.

PERFECT IMAGE PRISM PRINTER & AUTOPRINTER SPECIFICATIONS

PRINTING METHOD

Thermal transfer line printer

PRINT MODES

Single pass or double pass for improved print quality on some media types

PRINT RESOLUTION

WIN 95/98 300 x 300 dpi
WIN 2000/NT 300 x 600 dpi

NOMINAL MEDIA DIAMETER

120mm (4.73 inches)

EFFECTIVE PRINT AREA

115mm (4.5 inches)

MEDIA TYPES

Standard CD-R/CD-ROM—includes pre-screened

PHYSICAL

6"H x 8.5"W x 16"D (152.4mm H x 215.9mm W x 406.4mm D) 20 lbs. (9.1Kg)

INTERFACE

Centronics Parallel, Serial

POWER

100-240 VAC, 60/50 Hz, 1.1–.55 Amps auto ranging

OPERATING TEMPERATURE

60°F–90°F (15.5°C–35°C)

RELATIVE HUMIDITY

30%–80% non-condensing

SOFTWARE DRIVERS

Windows 95/98, Windows NT 3.51,
Windows NT 4.0, Windows 2000

CERTIFICATIONS

EMISSIONS FCC Class A (meets Class B)
EN55022 Class B

SUSCEPTIBILITY EN50082-1

SAFETY UL 1950, CAN C22.2 No. 950, EN 60950

CONFORMANCE MARKS UL, cUL, CE

WARRANTY

Six months from invoice

SERVICE OPTIONS

Various Rimage Service Programs are available. Contact your local Rimage Service Representative for details.

LABEL EDITOR SOFTWARE

Perfect Image CD Designer for Windows included

RIBBON COLOR

CYM Ribbon and Black Ribbon included

SYSTEM REQUIREMENTS

WIN 95 OR GREATER For best results Win2000 or NT should be used
PENTIUM OR GREATER Minimum 16MB RAM

Rimage Corporation leads the world in developing and manufacturing automated media replication and mass customization solutions. Rimage products serve diverse markets with applications for business-to-consumer entertainment and photography, government, business-to-business financial, health care, and manufacturing. In fact, we created the market for customized, on-demand data distribution. Rimage is at the focal point where innovative design, unparalleled robotics and integrated software converge.



R I M A G E™

Rimage Corporation
7725 Washington Avenue South
Minneapolis, MN 55439 USA
phone: 952.944.8144
fax: 952.944.7808

Rimage Europe GmbH
Hans-Bockler-Straße 7
63128 Dietzenbach
Germany
phone: 49.0.6074.8521.0
fax: 49.0.6074.8521.21

www.rimage.com

©Rimage Corporation 2000
All rights reserved
160086-001

Specifications subject to change without notice.